

## Face Material

### Coated Steel

#### Substrate

A substrate of hot dipped galvanised coated steel or aluminium zinc coated steel giving excellent corrosion resistance is used. Steel facings are generally available in 0.5, 0.55, 0.6 and 0.7mm thickness.

#### Primer

A 10 micron grey epoxy finish used predominantly for unseen surfaces. Can be painted or bonded with appropriate adhesives.

#### Anti Static White Food safe PVC Laminate

Generally a 120 micron thick coating of PVC film. Finish is chemically inert, stain and mould resistant, suitable for continuous contact with foodstuffs. Colours other than white may be available on request.

#### Architectural Polyester

Suitable for external use. A 25 micron coloured paint finish.




#### ArcelorMittal Standard Colour Range



Fish Eagle White



Azure Blue



White Lion



Buffalo Brown



Sandstone Beige



Aloe Green



Gemsbok Sand



Traffic Green



Umhlanga Wave



Dove Grey



Kingfisher Blue



Dark Dolphin



Kalahari Red



Charcoal Grey

Note: The colours may not display correctly due to individual screen settings. Different print technology may also result in colour variation when printing this Data Sheet. The Colour Chart displayed above is in reference to the Colour Chart available from ArcelorMittal South Africa. ArcelorMittal South Africa Limited does not assume responsibility for any inaccuracies or misrepresentations of this data.

All data conforms to current best practice and is for guidance only. For specific conditions of use please refer to our Technical Department. Isowall Southern Africa reserves the right to alter specifications without prior notice.

#### CONTACT DETAILS:

326 Derdepoort Road, Silverton | (012) 804 3564 | [info@isowall.co.za](mailto:info@isowall.co.za) | [www.isowall.co.za](http://www.isowall.co.za)